


## Pin strip for SMD


### 931-SLR-SMD-1,3

Plug-in area  $\varnothing$  1,3 mm



$$L1 = (\text{No. of poles} - 1) \times \text{pitch}$$

### PCB Layout



Solder paste thickness: 0,15 - 0,2 mm

931-SLR-SMD is a pin strip with 3,5 mm pitch for the application in a reflow soldering process. Contrary to the pin strips 931-SLR-THR and 931-SLR-THR-1,3, for which holes in the PCB are necessary, the SMD types of WECO base on true surface assembly. Soldering expanses at the end of the pins guarantee optimal retention force on the printed circuit board.

The pin strip 931-SLR-SMD-1,3, comes with a constant pin  $\varnothing$  of 1,3 mm at the plug-in area.

Just like all THR versions of WECO, also the housings of the SMD series are made out of high temperature resistant plastic material and exhibit a very high CTI value.

For the automatic assembling all pin strips of this series are packed in Tape on Reel and equipped with high temperature resistant pick caps, which can easily be removed after the soldering process.

### Part Numbers

No. of poles	931-SLR-SMD-1,3	Length	Pcs
2	12.893.731	6,50	1000
3	13.893.731	10,00	1000
4	14.893.731	13,50	500
6	16.893.731	20,50	500
8	18.893.731	27,50	250
10	20.893.731	34,50	200
12	22.893.731	41,50	200
16	26.893.731	55,50	200

further number of poles on request

### General Information

Centre to centre spacing	3,5 mm
No. of poles	2 - 16
Usable with	plugs 938-FLDS
Additional Information	Also, please take into consideration the pin strips 931-SLS for wave soldering and series 931-SLR-THR for Through-Hole-Reflow.

### Technical Data

Overvoltage Category	III	III	II
Pollution Severity Level	3	2	2
Rated Voltage	160 V	160 V	320 V
Rated Impulse Voltage	2,5 kV	2,5 kV	2,5 kV
Rated Insulation Voltage	130 V acc. to EN 60998-1		
Rated Current	6 A		
Soldering process	Reflow solder		

### Material

Moulding	PA HT, black, V-0
Comparative Tracking Index	CTI $\geq$ 600
Insulating Group	I
Temperature Range	-40°C up to 150°C; reflow solder temperature (Peak) max. 260°C (15-30 s)
Solder pin	$\varnothing$ 1,3 mm (plug-in area); tin plated brass

### Approvals

	Current	Voltage	Group	AWG	Nm
	6	150	B		
	6	300	D		
	6	150	B		
	6	300	D		

### Options / Accessories

- Other plug pin lengths on request
- Other solder pin surfaces on request

### Part Numbers: Tape-on-Reel

No. of poles	931-SLR-SMD-1,3	Tape Width	Tape Height	Pcs
3	13.893.731.A00	32 mm	14,6 mm	500
4	14.893.731.A00	32 mm	14,6 mm	500
5	15.893.731.A00	32 mm	14,6 mm	500
6	16.893.731.A00	56 mm	14,6 mm	500
7	17.893.731.A00	56 mm	14,6 mm	500
8	18.893.731.A00	56 mm	14,6 mm	500
9	19.893.731.A00	56 mm	14,6 mm	500
10	20.893.731.A00	56 mm	14,6 mm	500
11	21.893.731.A00	56 mm	14,6 mm	500
12	22.893.731.A00	72 mm	14,9 mm	500
13	23.893.731.A00	72 mm	14,9 mm	500
14	24.893.731.A00	72 mm	14,9 mm	500

further number of poles on request